



1

<b>Pneumatic - Spring</b>	3/2	Ordering code <b>212.1.11.1</b>	5/2	<b>Pneumatic - Spring</b>			
 		<b>T</b> TYPE 32 = 3 ways 52 = 5 ways	 				
		Weight gr. 1110 Minimum piloting pressure 2,5 bar			 Weight gr. 1390 Minimum piloting pressure 2,5 bar		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"

<b>Pneumatic - Differential external</b>	3/2	Ordering code <b>212.1.11.12</b>	5/2	<b>Pneumatic - Differential external</b>			
 		<b>T</b> TYPE 32 = 3 ways 52 = 5 ways	 				
		Weight gr. 1380 Minimum piloting pressure 2,5 bar			 Weight gr. 1660 Minimum piloting pressure 2,5 bar		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"


<b>Pneumatic - Pneumatic</b>	3/2	Ordering code <b>212.1.11.11</b>	5/2	<b>Pneumatic - Pneumatic</b>			
 		<b>T</b> TYPE 32 = 3 ways 52 = 5 ways	 				
		Weight gr. 1350 Minimum piloting pressure 2 bar			 Weight gr. 1630 Minimum piloting pressure 2 bar		
<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature	Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C Max. +70°C	3500 NI/min	mm 15	G 1/2"	G 1/8"



**Pneumatic - Pneumatic**

5/3

Ordering code
<b>212.53.11.11</b>
FUNCTION
31 = Closed centres
32 = Open centres
33 = Pressured centres



Weight gr. 1650  
Minimum piloting pressure 3 bar



Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air		Min. -5°C	Max. +70°C				
		10 bar			3000 NI/min	mm 15	G 1/2"	G 1/8"





1

<b>Pneumatic - Spring</b>	3/2	Ordering code <b>212/2.1.11.1</b>	5/2	<b>Pneumatic - Spring</b>			
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td><b>T</b> 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	<b>T</b> 32 = 3 ways	52 = 5 ways		
			TYPE				
<b>T</b> 32 = 3 ways							
52 = 5 ways							

<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3600 NI/min	mm 15	G 1/2"	G 1/8"

<b>Pneumatic - Differential</b>	3/2	Ordering code <b>212/2.1.11.12</b>	5/2	<b>Pneumatic - Differential</b>			
<i>Diff. external - N.C.</i>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td><b>T</b> 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	<b>T</b> 32 = 3 ways	52 = 5 ways		<i>Diff. external</i>
TYPE							
<b>T</b> 32 = 3 ways							
52 = 5 ways							
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td><b>T</b> 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> </table>	TYPE	<b>T</b> 32 = 3 ways	52 = 5 ways		
			TYPE				
<b>T</b> 32 = 3 ways							
52 = 5 ways							

<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3600 NI/min	mm 15	G 1/2"	G 1/8"

<b>Pneumatic - Differential</b>	3/2	Ordering code <b>212/2.1.11.12/C</b>	5/2	<b>Pneumatic - Differential</b>						
<i>Diff. self aligned</i>		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td><b>T</b> 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> <tr><td>1.C = 3 ways Norm. closed</td></tr> <tr><td><b>C</b> 1.A = 3 ways norm. open</td></tr> <tr><td>1 = 5 ways diff. self aligned</td></tr> </table>	TYPE	<b>T</b> 32 = 3 ways	52 = 5 ways	1.C = 3 ways Norm. closed	<b>C</b> 1.A = 3 ways norm. open	1 = 5 ways diff. self aligned		<i>Diff. self aligned</i>
TYPE										
<b>T</b> 32 = 3 ways										
52 = 5 ways										
1.C = 3 ways Norm. closed										
<b>C</b> 1.A = 3 ways norm. open										
1 = 5 ways diff. self aligned										
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr><td>TYPE</td></tr> <tr><td><b>T</b> 32 = 3 ways</td></tr> <tr><td>52 = 5 ways</td></tr> <tr><td>1.C = 3 ways Norm. closed</td></tr> <tr><td><b>C</b> 1.A = 3 ways norm. open</td></tr> <tr><td>1 = 5 ways diff. self aligned</td></tr> </table>	TYPE	<b>T</b> 32 = 3 ways	52 = 5 ways	1.C = 3 ways Norm. closed	<b>C</b> 1.A = 3 ways norm. open	1 = 5 ways diff. self aligned		
			TYPE							
<b>T</b> 32 = 3 ways										
52 = 5 ways										
1.C = 3 ways Norm. closed										
<b>C</b> 1.A = 3 ways norm. open										
1 = 5 ways diff. self aligned										

<b>Operational characteristics</b>	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with $\Delta p=1$	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3600 NI/min	mm 15	G 1/2"	G 1/8"



1

<b>Pneumatic - Pneumatic</b>	3/2	Ordering code <b>212/2.1.11.11</b>	5/2	<b>Pneumatic - Pneumatic</b>				
		<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="text-align: center;">TYPE</td> </tr> <tr> <td>32 = 3 ways</td> </tr> <tr> <td>52 = 5 ways</td> </tr> </table>		TYPE	32 = 3 ways	52 = 5 ways		
				TYPE				
32 = 3 ways								
52 = 5 ways								
Minimum piloting pressure 2,5 bar				Minimum piloting pressure 2,5 bar				

Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with Δp=1	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3600 NI/min	mm 15	G 1/2"	G 1/8"

<b>Pneumatic - Pneumatic</b>	5/3										
<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="padding: 2px;">Ordering code</td> <td style="text-align: center;"><b>212/2.53.F.11.11</b></td> </tr> <tr> <td style="padding: 2px;">FUNCTION</td> <td></td> </tr> <tr> <td style="padding: 2px;">F 31 = Closed centres</td> <td></td> </tr> <tr> <td style="padding: 2px;">32 = Open centres</td> <td></td> </tr> <tr> <td style="padding: 2px;">33 = Centri in pressione</td> <td></td> </tr> </table>		Ordering code	<b>212/2.53.F.11.11</b>	FUNCTION		F 31 = Closed centres		32 = Open centres		33 = Centri in pressione	
Ordering code	<b>212/2.53.F.11.11</b>										
FUNCTION											
F 31 = Closed centres											
32 = Open centres											
33 = Centri in pressione											
Minimum piloting pressure 3 bar											

Operational characteristics	Fluid	Max working pressure	Operating Temperature		Flow rate at 6 bar with Δp=1	Orifice size	Working port size	Pilot port size
	Filtered and lubricated air	10 bar	Min. -5°C	Max. +70°C	3300 NI/min	mm 15	G 1/2"	G 1/8"